

## HT-AE-630 BATTERY POWERED HEAT ALARM

<b>Sensor type</b>	Thermistek Class A1 heat detection
<b>Battery type</b>	10 year sealed for life lithium



- Thermistek technology, incorporating a unique radiant heat dish.
- Class A1 device.
- 10 year sealed for life lithium battery.
- Large central button - test or silence.
- Silence function - allows the alarm to be silenced in the event of a known false alarm.



## Technical Specification

<b>Dimensions</b>	132mm (diameter) x 60mm (depth)	
<b>Supply voltage</b>	3V DC	
<b>Battery</b>	10 year sealed for life lithium battery	
<b>Technology</b>	Thermistek	
<b>Alarm sound level</b>	85dB(A) at 3m (minimum)	
<b>Installation positions</b>	Ceiling	
<b>Alarms at temperature range</b>	+54°C to +62°C	
<b>Operating temperature</b>	+4°C to +38°C	
<b>Operating humidity</b>	Up to 90% RH non-condensing	
<b>Storage temperature</b>	-20°C to +60°C	
<b>Storage humidity</b>	Up to 93% RH non-condensing	
<b>Plastic material</b>	ABS, UL94 VO fire retardant	
<b>Warranty</b>	5 years	
<b>Weight</b>	177g	
<b>Certified to</b>	BS 5446-2: 2003	
<b>Independently tested to</b>	N/A	
<b>Maximum number of connected units</b>	N/A	
<b>Operating Frequency</b>	N/A	
<b>Range</b>	N/A	